



Leading-edge. That's what Huebsch® stands for. We continuously develop and manufacture laundry equipment that is ahead of the game—like new front load washers with our leading Galaxy™ 600 controls, featuring advanced cycle modifiers to maximize your revenue. These machines offer a 20% larger capacity, and they're more powerful than ever. Our engineers push them to the limit using our 5-step development process to ensure maximum commercial performance and reliability. They're equipped with innovation that delivers ultimate efficiency, lowering your utility bills and making more money for you over the lifetime of your equipment. For customers, this game-changing equipment is designed to provide a laundry experience that is second to none.



## CUTTING-EDGE BALANCE SENSING SYSTEM

An updated suspension and new sensing technologies powerfully combine to redistribute loads and maintain cycle times—resulting in less utility costs, shorter wait times and increased turns through your store.

## INCREDIBLE 440 G-FORCE

Increased spin speed exerts high G-Force to maximize moisture removal and lower drying times, getting customers in and out of your store faster and ensuring they leave satisfied.

## 20% LARGER CAPACITY

Increased capacity means bigger loads, which allow for higher vend pricing. In addition, improved water and energy efficiencies lower utility bills and keep more money in your pocket.

## 10-DEGREE TILTED CONTROL PANEL

Provides improved control visibility and ease of use for the utmost user experience.

## INNER & OUTER STAINLESS STEEL TUBS

Built for virtually indestructible durability.

## UNMATCHED DURABILITY

Commercial-grade quality that will deliver reliable, efficient operation load after load. Built with premium materials and tested to meet the demands of the harshest environments, the entire machine receives Huebsch's standard three-year warranty.\*

## GALAXY™ 600 CONTROLS



Easy-to-use Galaxy 600 controls offer intuitive operation and simple programming throughout your store with revenue-boosting options such as cycle modifiers (extra wash, extra rinse), multi-level vend, time-of-day pricing, 30 programmable water levels and 24 customizable cycle selections.

# VENDED FRONT LOAD WASHER



Specifications	Front Control			Rear Control
Galaxy™ 600 Controls Slate - White	Models HFNKCASP113TW01 HFNKDASP113CW01 HFNKXASP113CW01	HFNKYASP113CW01 HFNKCASG113TW01 HFNKDASG113CW01	HFNKXASG113CW01 HFNKYASG113CW01	
Galaxy 600 Controls Slate - Stainless Steel	Models HFNKCASP113TN01 HFNKDASP113CN01 HFNKXASP113CN01	HFNKYASP113CN01 HFNKCASG113TN01 HFNKDASG113CN01	HFNKXASG113CN01 HFNKYASG113CN01	
Galaxy 600 Controls Cityscape - Stainless Steel	Models HFNKCASP113TN31 HFNKDASP113CN31 HFNKXASP113CN31	HFNKYASP113CN31 HFNKCASG113TN31 HFNKDASG113CN31	HFNKXASG113CN31 HFNKYASG113CN31	
Galaxy 600 Controls Citron - Stainless Steel	Models HFNKCASP113TN32 HFNKDASP113CN32 HFNKXASP113CN32	HFNKYASP113CN32 HFNKCASG113TN32 HFNKDASG113CN32	HFNKXASG113CN32 HFNKYASG113CN32	
MDC Controls	Models HFNBCASP113TW01 HFNBCASG113TW01 HFNBCASP113TN01 HFNBCASG113TN01	HFNBYPASP113CW01 HFNBYPASG113CW01 HFNBBDASP113CW01 HFNBBDASG113CW01	HFNBEPASP113CW01 HFNBXPASP113CW01	Models HFNBCRSP113TW01 HFNBYSRSP113CW01 HFNBDRSP113CW01 HFNBERSP113CW01
Coin Slide Controls				Models HFNSXRSP113CW01
Capacity - lb (kg)	21.5 (9.5)			21.5 (9.5)
Cylinder Volume - cu. ft. (liters)	3.42 (96.8)			3.42 (96.8)
Width - in (mm)	26 7/8 (683)			26 7/8 (683)
Depth - in (mm)	27 3/4 (704)			27 3/4 (704)
Height - in (mm)	44 3/8 (1126)			43 (1092)
Maximum Spin Speed - G-Force (RPM)	440 (1200)			440 (1200)
Motor Size - HP (kw)	Variable Speed Induction 0.9 (0.67)			Variable Speed Induction 0.9 (0.67)
Water Consumption per Cycle* - g (l)	11.7 (44.3)			11.7 (44.3)
WF (Water Factor)	3.8			3.8
MEF (Modified Energy Factor)	2.98			2.98
Available Water Temperatures	3			3
Available Cycles*	Hot, Warm, Cold, Blankets, Delicate Warm, Delicate Cold			Normal, Perm Press, Delicate
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)			20-120 (1.4/8.3)
Cycle Indicator Lights	Yes			Yes
Cylinder Finish	Stainless Steel			Stainless Steel
Available Colors	White, Stainless Steel			White
Door Type (Solid/Window)	Window			Window
Available Electrical Requirements - (Voltage/Hz/Ph)	120/60/1 - 15 Amp			120/60/1 - 15 Amp
Net Weight - lb (kg)	270 (122)			253 (115)
Shipping Weight - lb (kg)	290 (132)			273 (124)
Shipping Width - in (mm)	29 (737)			29 (737)
Shipping Depth - in (mm)	32 3/4 (832)			32 3/4 (832)
Shipping Height - in (mm)	45 1/2 (1156)			45 1/2 (1156)
Available Agency Approvals	C <sup>U</sup> L <sup>U</sup> S			C <sup>U</sup> L <sup>U</sup> S

\* Information shown applies to highest end control available.  
 Note: Not all options are available for all models. Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US.  
 Refer to the price list for the available models and options.  
 Front control unit is ADA Compliant.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2015 Alliance Laundry Systems LLC

AH15-0034

Alliance Laundry Systems LLC, Shepard Street, Ripon, WI 54971, 1-800-553-5120 huebsch.com

